

Suite 301, One Westlakes, Berwyn P.O. Box 980

Valley Forge, PA 19482-0980 Phone: 610-407-0700 Fax: 610-407-0701 Nemours Building 1007 Orange Street, Sulte 1100 P.O. Box 1596 Wilmington, DE 19899 Phone: 302-778-2500

www.ratnerprestia.com

302-778-2600

Suite 265
Commerce Corporate Center
5100 Tilghman Street
Allentown, PA 18104
Phone: 610-530-8100
Fax: 610-530-8200

## FACSIMILE COVER SHEET

DATE: October 16, 2003

OUR REF.:

IBME-050US1

TIME: 2:30 p

YOUR REF .:

10/001,421

TO: Examiner Vu

COMPANY: U.S. Patent & Trademark Office

Fax:

FROM: Daniel N. Calder (Reg. No. 27,424)

FAX TELEPHONE: (703) 746-3888

OFFICE TELEPHONE:

TITLE OF DOCUMENT: PI

Proposed Amendments

Total Number of Pages: 2 (Including this form)

COMMENTS

Dear Examiner Vu:

Further to our telephone conversation of today, I enclose a copy of a proposed amended claim 11. I look forward to our telephone interview on Wednesday, October 22, 2003, at 2:00 p.m.

Best regards,

Danil N. Corde

Daniel N. Calder

## CONFIDENTIAL AND PRIVILEGED ATTORNEY/CLIENT INFORMATION

This facsimile transmission (and/or documents accompanying it) may contain attorney/client privileged communications and confidential business information that is intended for use only by the individual or company to whom it is addressed. Disclosure, interception, copying or any other use of this transmission by anyone other than any intended recipient is prohibited. If you receive this transmission by mistake, please notify the sender.

Please notify us immediately if you have not received the number of pages indicated above.

Appln. No.: 10/001,421

Atty. Docket No.: END919970013US2

## PROPOSED AMENDMENTS

- 11. (Currently Amended) An interconnect structure for a semiconductor chip comprising:
  - a nonreflowed solder assembly including;\_;
- a Pb-rich ball attached to said semiconductor chip and having an exposed surface; and
  - a thin cap layer of Sn on said exposed surface of said Pb-rich ball;

said Sn layer being-sufficiently thin having a thickness of less than 10.2µm (0.4 mils) and having a melting temperature-lower than that of Pb so that Sn from said thin layer and Pb from said ball are uniformly diffused and intermixed after reflowing and annealing to form [[an]] a solder assembly having a weight composition of about 97/3-Pb/Sn.

12.-14. (Cancelled)